

PA66 for Broad and Narrow Weaving, Sewing Threads applications

TYP	Product	Heat resistant	Light protected	Titer		Breaking Strength		Tenacity		Elongation (%)	FASE 5% (N)	H. air sh. Nexis (%)	H. air sh. BISFA (%)	BWS 95°C (%)	IMG (kn./m)	Oil (%)	Tube (mm)	Weight		Diam. (mm)
				(dtex)	(Den)	(N)	(lbf)	(cN/Tex)	(gpd)									(g)	(lbs)	
640	117 f 17	X	X	120	108	7.5	1.7	62.5	7.1	18.7	2.1	10.6	8.7	7.0	20	0.70	Y94/290	4300	9.5	220
641	235 f 34	X	X	235	212	17.5	3.9	74.5	8.4	17.6	4.2	9.6	7.5	6.7	30	0.55	Y94/290	9060	20.0	280
634	235 f 34	X°	X	235	212	17.5	3.9	74.5	8.4	18.0	3.9	10.0	8.0	7.0	30	0.50	Y94/290	9280	20.5	280
634	470 f 68	X°	X	472	425	34.5	7.8	74.5	8.4	18.0	7.4	10.0	8.0	7.0	30	0.50	Y94/290	9160	20.2	280
633	235 f 34	X°	X	235	212	17.5	3.9	74.5	8.4	20.0	3.0	5.7	4.0	3.3	20	0.50	Y94/290	9270	20.4	280
633	470 f 68	X°	X	468	421	34.5	7.8	74.5	8.4	20.0	6.0	5.7	4.0	3.3	20	0.50	Y94/290	9160	20.2	280
632	110 f 17	X°	X	110	99	7.8	1.8	70.9	8.0	19.0	1.4	5.7	4.0	3.1	26	0.60	Y94/290	4500	9.9	215
632	110 f 34	X°	X	110	99	7.1	1.6	64.5	7.3	21.0	1.4	5.7	4.0	3.3	26	0.60	Y94/290	4300	9.5	225
632	235 f 34	X°	X	235	212	17.4	3.9	74.0	8.4	20.0	3.0	5.7	4.0	3.4	30	0.50	Y94/290	9270	20.4	280
632	470 f 68	X°	X	471	424	34.5	7.8	73.2	8.3	20.0	6.0	5.7	4.0	3.2	28	0.50	Y94/290	9160	20.2	272
Under development																				
632	156 f 34	X	X	159	143	12	2.7	74.0	8.4	18.7	2.1	5.7	4.0	-	30	0.60	Y94/290	9000	19.8	280
632	312 f 68	X	X	310	279	24	5.3	74.0	8.4	21.3	3.7	5.7	4.0	-	30	0.50	Y94/290	9000	19.8	280
642	110 f 34	X	X	110	99	7	1.6	63.5	7.2	22.0	1.5	5.7	4.0	-	30	0.55	Y94/290	9000	19.8	280
642	235f34	X	X	236	212	18	3.9	74.0	8.4	20.0	3.2	5.7	4.0	-	30	0.50	Y94/290	4600	10.1	230
642	470f68	X	X	472	425	35	7.8	74.0	8.4	20.8	6.2	5.7	4.0	-	30	0.61	Y94/290	4600	10.1	230
6563	125 f 17	X	X	125	113	3	0.6	22.0	2.5	260	-	-	-	-	-	0.80	Y94/290	3500	7.7	180

(°): For high demanding thermal resistance applications, please contact our Technical Support




R15-02

Packaging

Packing ID	Pallet				Yarn Type
	LxWxH	No. of boxes	No. of cylinders	Gross weight (kg)	
PT1-01	1200x800x1050	-	33	360	T632, T633, T634, T641, T642
PT6-01	1200x800x1050	-	48	290	T632, T634, T640, T641, T642

Note: Non-standard packaging is subject to special agreement.



PT1-01, PT6-01, PS1-01, V11-02



All types and counts can be delivered plied and twisted, or Air-jet textured.