

PA66 for Broad and Narrow Weaving, Sewing Threads applications

TYP	Product	Heat resistant	Light protected	Titer		Breaking Strength		Tenacity		Elongation	FASE 5%	H. air sh.	BWS	IMG	Oil	Tube	Weight		Diam.
				(dtex)	(Den)	(N)	(lbf)	(cN/Tex)	(gpd)								(%)	(N)	
640	117 f 17	X	X	120	108	7.5	1.7	63	7.1	18.7	2.1	8.7	7.0	20	0.70	Y94/290	4300	9.5	220
632	110 f 17	X°	X	110	99	7.7	1.7	70	7.9	19.5	1.5	4.3	3.1	26	0.60	Y94/290	4500	9.9	215
632	110 f 34	X°	X	110	99	7.1	1.6	65	7.3	21.0	1.4	4.3	3.3	26	0.60	Y94/290	4300	9.5	225
632	235 f 34	X°	X	235	212	17.4	3.9	74	8.4	19.5	3.0	4.3	3.4	27	0.50	Y94/290	9270	20.4	280
632	470 f 68	X°	X	471	424	34.5	7.8	73	8.3	20.0	6.0	4.2	3.2	27	0.50	Y94/290	9160	20.2	280
633	235 f 34	X°	X	235	212	17.5	3.9	74	8.4	20.0	3.0	4.3	3.3	15	0.50	Y94/290	9270	20.4	280
633	470 f 68	X°	X	468	421	34.5	7.8	75	8.4	20.0	6.0	4.2	3.3	15	0.50	Y94/290	9160	20.2	280
634	235 f 34	X°	X	235	212	17.5	3.9	74	8.4	18.0	3.9	8.0	7.0	30	0.50	Y94/290	9280	20.5	280
634	470 f 68	X°	X	472	425	34.5	7.8	75	8.4	18.0	7.4	8.0	7.0	30	0.50	Y94/290	9160	20.2	280
641	235 f 34	X	X	235	212	17.2	3.9	73	8.3	17.6	4.2	7.5	6.7	30	0.55	Y94/290	9060	20.0	280
642	235 f 34	X	X	236	212	17.5	3.9	74	8.4	20.0	3.1	4.3	-	27	0.50	Y94/290	4600	10.1	230
Under development																			
632	156 f 34	X	X	159	143	12	2.7	74	8.4	18.7	2.1	4.0	-	30	0.60	Y94/290	9000	19.8	280
632	312 f 68	X	X	315	284	24	5.3	74	8.4	21.3	3.7	4.4	-	30	0.50	Y94/290	9000	19.8	280
642	110 f 34	X	X	110	99	7.2	1.6	65	7.4	22.0	1.5	4.6	-	26	0.55	Y94/290	4300	9.5	225
642	470 f 68	X	X	472	425	35	7.8	74	8.4	20.8	6.2	4.0	-	30	0.61	Y94/290	4600	10.1	230
6563	125 f 17	X	X	125	113	3	0.6	22	2.5	260	-	-	-	-	0.80	Y94/290	3500	7.7	180
681	235 f 34	X	X	235	212	17.2	3.9	73	8.3	24.5	2.6	6.6	-	20	0.50	Y75/290	10000	22.0	270
683	235 f 34	X	X	240	216	17.1	3.8	71	8.1	24.1	2.4	4.0	-	21	0.50	Y75/290	10000	22.0	270
683	470 f 68	X	X	480	432	34	7.7	71	8.1	23.8	4.9	4.2	-	21	0.50	Y75/290	10000	22.0	270


(°): For high demanding thermal resistance applications, please contact our Technical Support



R15-02

Packaging					
Packing ID	Pallet				Yarn Type
	LxWxH	No. of boxes	No. of cylinders	Gross weight (kg)	
PT1-01	1200x800x1050	-	33	360	T632, T633, T634, T641, T642
PT6-01	1200x800x1050	-	48	290	T632, T634, T640, T641, T642

Note: Non-standard packaging is subject to special agreement.



PT1-01, PT6-01, PS1-01, V11-02



All types and counts can be delivered plied and twisted, or Air-jet textured.