

PA6 Spun dyed Neon Colors for Ropes, Nets & Weaving applications

bluesign®
APPROVED

TYPE	Product	Heat resistant	Light protected	Titer		Breaking Strength		Tenacity		H. air sh.	BWS	IMG	Oil	Tube	Weight		Diam.
				(dtex)	(Den)	(N)	(lbf)	(cN/Tex)	(gpd)						(g)	(lbs)	
052	940 f 136 - NXXX	-	X	940	846	71.4	16.1	76	8.6	9.5		20	1.00	Y73/292	9100	20.1	255
Under development																	
052	1400 f 204 - NXXX	-	X											Y73/292	9100	20.1	255
052	1880 f 272 - NXXX	-	X											Y73/292	9100	20.1	255
052	2100 f 272 - NXXX	-	X											Y73/292	9100	20.1	255

The characteristics can vary from 1 color to another

Colour	Rub-Fastness - Crockmeter (1-5 grey scale)	Wet-Fastness (1-5 grey scale - shade fading / Stain on PA* / Stain on WO**)		Light-Fastness (1-8 on blue scale after 300h)
		STN EN ISO 105-X12		
Color codes	Dry	Wet		
N - 115 Neon Yellow	4-5	3-4		3-4
N - 255 Neon Orange	5	4-5		2
N - 325 Neon Pink	4	4		2
N - 635 Neon Green	4-5	4		2


*- polyamide fabric, **- wool fabric

It is recommended to check the fastness properties on the final product.

For end-uses that are particularly sensitive to wet fastnesses, or with very high light fastness requirements, please consult with Nexis-Fibers' Technical Support Team.

Packaging			
Packing ID	Pallet		
	LxWxH	No. of cylinders	Gross weight (kg)
P12-07	1100x800x1700	60	600

Note: Non-standard packaging is subject to special agreement.



P12-07



All colors can be delivered plied and twisted, or Air-jet textured. Please contact the Technical Support for all inquiries.